



CL226



CL226-1



CL226-2



CL226-3



CL226-2A



Main material and finish: Black powder coated ZDC hinge, nickel-plated steel pin
Application: Opening angle 180°

Performance parameter:

Maximum static load

Model: CL226-1

Radial load: 1500N Axial load: 1800N

Model: CL226-2

Radial load: 1200N Axial load: 1300N

Model: CL226-3

Radial load: 1000N Axial load: 1200N

Model: CL226-2A

Radial load: 1200N Axial load: 1300N

Embedded screw recommended

tightening torque : 10N.m

Model	ERP	Specification							Remark
		A	B	C	D	E	F	G	
CL226-1	CL226Z1A001	36	60	16.5	8.4	8	15	8	Countersunk hole,ZDC
CL226-1A	CL226Z1A006	36	60	16.5	8.4	8	15	8	Screw embedded, ZDC
CL226-1B	CL226S9C001	36	60	16.5	8.4	8	15	8	Countersunk hole, stainless steel
CL226-2	CL226Z1A009	30	50	12.5	6.3	6	11.5	6	Countersunk hole,ZDC
CL226-2A	CL226Z1A010	30	50	Refer to detailed drawing	6	11.5	6	6	Screw embedded, ZDC
CL226-2C	CL226Z1A011	30	50	Refer to detailed drawing	6	11.5	6	6	Step hole,ZDC
CL226-2S	CL226N00001	30	50	12.5	6.3	6	11.5	6	Countersunk hole,PA
CL226-2B	CL226S4B001	30	50	12.5	6.3	6	11.5	6	Countersunk hole, stainless steel
CL226-3	CL226Z1A015	25	40	10.2	5.3	5	9	4	Countersunk hole,ZDC
CL226-3A	CL226Z1A017	25	40	10.2	5.3	5	9	4	Screw embedded, ZDC

Accessories

Electronic lock

Handle lock

Cylinder lock

Plane lock

Rod control lock

Panel lock

Toggle and hook

Handles

Door stop

Hinge

Seal gasket